

gx 1 specs



The future of live show design

The unrivalled combination of power, size and affordability you get from gx 1 gives you full access to the generative content world.

Warranties & Support

– 2 year return to base hardware warranty (plus options to extend warranty length)


Bundled accessories

Keyboard, Mouse & Pad, Power Cable (Plug-True1), Power Daisy Chain (True1-True1), Active DP to DVI adapter, Getting Started Guide, Backmounted Rails.

Physical specifications

Packed Dimensions:	W 711mm 28"	H 270mm 10.62"	D 737mm 29"
Unit Dimensions:	W 445mm 17.52"	H 88.9mm 3.5"	D 593mm 23.35"
Unit + Rack Handles	W 483mm 19"		D 621mm 24.45"
Rack Depth:			D 585mm 23.03"
Unit Weight:		10.8kg	23.8lbs
Packed Unit Weight:		18.6kg	41lbs

gx 1 specs



Hardware specifications

Voltage: 100-240V, 50Hz - 60Hz

Power Consumption:

400VA @ 240V, 50Hz

Operating System: Windows 10 IoT

Enterprise LTSC

CPU: Intel® Xeon® Quad-Core 3.7Ghz

Memory: 16GB DDR4 RAM

Environmental Tolerances:

Temperature: 5-35°C (40°-95°F)

Humidity: 5%-95% (non-condensing)

Altitude: 0-8850 ft (0-2700m)

Mounting System:

2U 19" rack mount

OS: 2x 80GB SSD

(Internal System Drive, Restore Drive)

Storage: 2TB SSD

System connectivity I/O

Video Output:

1x DisplayPort 1.2 (GUI)

1x VFC Output Slot

Ships standard with DisplayPort 1.2 VFC card (4096 x 2160 max)

Different Video Format Conversions cards also available, refer to VFC Specifications

Video Input:

3x HD-SDI or 2x 3G-SDI

LTC Timecode:

1x Balanced XLR Input

Audio Out:

N/A (achievable through 3rd party software/devices)

General Network: 1x Gigabit LAN

Artnet: 1x Gigabit LAN

Media Network: 2x 10Gb/sec LAN

Data/Peripherals:

5x USB 3.0

Video Sync: BNC Genlock